

MULTI SPLIT DUCT AIR CONDITIONERS

NEVO



SAVA



ESP
up to 40Pa



ON/OFF
remote output



Alarm
output signal



CAV air flow
control



Compact
dimensions



SMART WiFi
function ⁽¹⁾



UNIT FEATURES



R32 ecological
refrigerant



SKY® DC motors



Digital DC
Inverter SKY®



Automatic
cleaning iAIR



Electrostatic
HD iAIR
filter



Turbo eMOTO
mode



Airflow control
system eMOTO



Wired controller
SMART port



Remote controller
⁽¹⁾



Wired controller



SMART Follow
mode⁽²⁾



Temperature
indemnification



Refrigerant
leak alarm



Emergency start
function



Auto restart
memory



Drip tray
heater ⁽⁴⁾



Compressor
crankcase
heater ⁽⁴⁾



Timer



Anti-corrosive
gold-plated fins



Heating
up to -15°C



Cooling
up to -15°C



Self-diagnosis
function



Double-sided
condensate
drainage



Sleep
function



Built-in
condensate
pump



Fresh air



Output to the
weekly controller



Output to the
central
controller



Adjustable static
pressure

1. Remote controller available as an option
2. Available using the optional MAZE wireless controller

3. Optional WiFi modem required
4. Available when connecting the indoor unit with the Hiro NORDIC unit

TECHNICAL DATA

Model			Nevo 2.1 kW	Nevo 2.6 kW	Nevo 3.5 kW	Nevo 5.3 kW	
Capacity	Cooling	Nominal	W	2051	2638	3517	5275
Power consumption		Nominal	W	40	40	40	90
Operating current		Nominal	A	1.0	0.17	0.17	0.39
Capacity	Heating	Nominal	W	2345	2931	3810	5861
Power consumption		Nominal	W	40	40	40	90
Operating current		Nominal	A	0.56	0.17	0.17	0.39
Dehumidification			l/h	1.0	1.1	1.2	1.9
Indoor unit			N21Wm	N26Wm	N35Wm	N50Wm	
Fan speed	(Hi/Mi/Lo.)	rpm	1080/920/790	1080/920/790	1080/920/790	1650/1300/1000	
Air flow	(Hi/Mi/Lo.)	m ³ /h	500/340/230	500/340/230	600/480/300	880/650/350	
Sound pressure level at standard rating conditions	(Hi/Mi/Lo.)	dB(A)	40/34.5/27.5	40/34.5/27.5	40/34/27	41.5/38/33	
Sound power level at standard rating conditions		dB(A)	58	58	59	59	
ESP - External static pressure	Standard	Pa	25	25	25	25	
	Range	Pa	0-40	0-40	0-60	0-100	
Net Dimensions	(WxDxH)	mm	700x450x200	700x450x200	700x450x200	880x674x210	
Gross dimensions	(WxDxH)	mm	860x540x275	860x540x275	860x540x275	1070x725x280	
Net weight / Gross weight		kg	18/22	18/22	18/22	24.3/29.6	
Pipe connections	Liquid / Gas	mm(inch.)	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ12.7 (1/4"/1/2")	
Condensate drain		mm	25	25	25	25	
Power supply outdoor unit		V-Hz, Ø	220-240-50, 1f	220-240-50, 1f	220-240-50, 1f	220-240-50, 1f	
Control cables: indoor - outdoor		qt. x mm ²	4 x 1.5	4 x 1.5	4 x 1.5	4 x 1.5	
Inside working range	(Cooling/Heating)	°C	17-32 / 0-30	17-32 / 0-30	17-32 / 0-30	17-32 / 0-30	
Outside working range	(Cooling/Heating)	°C	-15-50 / -15-24	-15-50 / -15-24	-15-50 / -15-24	-15-50 / -15-24	

OPTIONAL ACCESSORIES



Remote control
MAZE



Central wired
controller



Central wired controller
with weekly
programming



Filters



Modem
SMART WIFI



Alternate operation
controller

