

PORTABLE AIR CONDITIONERS

ORTA



- Ecological refrigerant R290
- Electrostatic HD iAIR filter
- Airflow control system eMOTO
- Wide angle air flow eMOTO
- Remote controller
- Louver settings memory
- Refrigerant leak alarm
- Auto restart memory
- Anti-corrosive gold-plated fins
- Timer
- Automatic evaporation
- Self-diagnosis function
- Automatic louver
- Sleep function

3 YEARS
WARRANTY

TECHNICAL DATA

Model				Orta 2.6 kW
Capacity	Cooling	Nominal	W	2638
Power consumption		Nominal	W	1000
Operating current		Nominal	A	4.35
Capacity	Heating	Nominal	W	-
Power consumption		Nominal	W	-
Operating current		Nominal	A	-
Energy efficiency class - cooling				A
Energy efficiency class - heating				-
EER / COP			W / W	2.6 / -
Dehumidification			l/h	2.6
Indoor unit				O26W
Fan speed	(Hi./Mi./Lo.)	rpm		650/550/450
Air flow	(Hi./Mi./Lo.)	m³/h		425/385/340
Sound pressure level at standard rating conditions	(Hi./Mi./Lo.)	dB(A)		45/44/43
Sound power level at standard rating conditions		dB(A)		56
Net Dimensions	(W×D×H)	mm		455×380×780
Gross dimensions	(W×D×H)	mm		535×480×885
Net weight / Gross weight		kg		31.1/36.2
Compressor type				Rotary DC
Refrigerant	Type			R290
	GWP			3
	Amount of refrigerant	kg		0.24
TCO _{eq}			0.0	
Condensate drain			mm	16
Power supply indoor unit			V-Hz, Ø	220-240-50, 1f
Overcurrent protection			A	C10
Inside working range		(Cooling/Heating)	°C	17-35/-